

MSP430 Advanced Technical Conference 2006




MSP430F2xx Family Enhancements and Features

Mike Mitchell
MSP430 Applications Engineer
Texas Instruments

Agenda

- Enhancements
- Application Examples
- Devices & Summary

MSP430 Products



MSP430F2xx – What's Different

- *Faster*
- *Lower power*
- *New peripherals*
- **Compatible migration path with the '1xx**
- **Great starting point for new applications**
- **Complete family of new devices planned**

MSP430F1xx Versus MSP430F2xx


	1xx	2xx
CPU Clock	8MHz	16MHz
Wakeup	6us	1us
Stand-by	<2uA	<1uA
BOR	Some	ALL
Flash ISP	2.7V	2.2V
P1/2	-	Pull-up / Down
Oscillator	±20%	±2.5%
OscFault	HF	HF/LF
Watchdog	SW	SW Invalid Address Clock Fault
BSL	2 ²⁵⁶	Hackproof

2X faster

1/2 power




Improved

F2xx 16MIPS On-Demand




F2xx Flash

- Fast <20us /byte ISP
- ISP down to 2.2V
- Interruptible ISP/Erase
- Reduced size 64B info memory segments
- Lock(able) info segment A
- Improved BSL security
- Protection against program/erase from accidental BSL entry



© 2006 Texas Instruments Inc, Slide 7

Achieving *Ultra-low Power*



- Max time in Ultra-low Power *LPM3* standby mode
- *Active* Performance on-demand
- Minimum active duty cycle

F2xx Basic Clock+


- **LFXT1 XTAL Oscillator**

- <1uA LPM3 standby mode
- XTAL CAPs programmable
- OSCfault LF/(XT)
- **New VLO**

- **Improved DCO**

- < 1us 0-to-16MHz
- $\pm 2.5\%$ DCO
- Programmable frequency

- **VLO not in '21x1**



F2xx: No XTAL Required – DCO+

calibrated DCO frequencies – tolerance at calibration

PARAMETER	TEST CONDITIONS	T _A	V _{CC}	MIN	TYP	MAX	UNIT
Frequency tolerance at calibration		25°C	3 V	-1	±0.2	+1	%

calibrated DCO frequencies – tolerance over temperature 0°C – +85°C

PARAMETER	TEST CONDITIONS	T _A	V _{CC}	MIN	TYP	MAX	UNIT
1 MHz tolerance over temperature		0–85°C	3.0 V	-2.5	±0.5	+2.5	%
8 MHz tolerance over temperature		0–85°C	3.0 V	-2.5	±1.0	+2.5	%
12 MHz tolerance over temperature		0–85°C	3.0 V	-2.5	±1.0	+2.5	%
16 MHz tolerance over temperature		0–85°C	3.0 V	-3.0	±2.0	+3.0	%

calibrated DCO frequencies – tolerance over supply voltage V_{CC}

PARAMETER	TEST CONDITIONS	T _A	V _{CC}	MIN	TYP	MAX	UNIT
1 MHz tolerance over V _{CC}		25°C	1.8 V – 3.6 V	-3	±2	+3	%
8 MHz tolerance over V _{CC}		25°C	1.8 V – 3.6 V	-3	±2	+3	%
12 MHz tolerance over V _{CC}		25°C	2.2 V – 3.6 V	-3	±2	+3	%
16 MHz tolerance over V _{CC}		25°C	3.0 V – 3.6 V	-3	±2	+3	%

calibrated DCO frequencies – overall tolerance

PARAMETER	TEST CONDITIONS	T _A	V _{CC}	MIN	TYP	MAX	UNIT
1 MHz tolerance overall		I: -40–85°C T: -40–105°C	1.8 V – 3.6 V	-5	±2	+5	%
8 MHz tolerance overall		I: -40–85°C T: -40–105°C	1.8 V – 3.6 V	-5	±2	+5	%
12 MHz tolerance overall		I: -40–85°C T: -40–105°C	2.2 V – 3.6 V	-5	±2	+5	%
16 MHz tolerance overall		I: -40–85°C T: -40–105°C	3.0 V – 3.6 V	-6	±3	+6	%

Slide 10

Loading DCO Calibration Data

DCO Calibration Data (provided from factory in flash info memory segment A)			
DCO Frequency	Calibration Register	Size	Address
1 MHz	CALBC1_1MHz	byte	010FFh
	CALDCO_1MHz	byte	010FEh
8 MHz	CALBC1_8MHz	byte	010FDh
	CALDCO_8MHz	byte	010FCh
12 MHz	CALBC1_12MHz	byte	010FBh
	CALDCO_12MHz	byte	010FAh
16 MHz	CALBC1_16MHz	byte	010F9h
	CALDCO_16MHz	byte	010F8h

```
BCSCTL1 = CALBC1_16MHZ;           // DCO = 16MHz  
DCOCTL = CALDCO_16MHZ;
```

VLO Specs

internal very low power, low frequency oscillator (VLO)


PARAMETER	TEST CONDITIONS	T _A	V _{CC}	MIN	TYP	MAX	UNIT
f _{VLO} VLO frequency		-40–85°C	2.2 V/3 V	4	12	20	kHz
		105°C	2.2 V/3 V			22	
df _{VLO} /dT VLO frequency temperature drift	(see Note 1)	I: -40–85°C T: -40–105°C	2.2 V/3 V		0.5		%/°C
df _{VLO} /dV _{CC} VLO frequency supply voltage drift	(see Note 2)	25°C	1.8V – 3.6V		4		%/V

- Wide initial tolerance
- Temperature drift
- Voltage drift

 **Calibratable, just like 1xx DCO!**

Calibrating the VLO

Calibrated 1 MHz DCO



- Clock Timer_A from calibrated 1MHz DCO
- Capture with rising edge of ACLK/8 from VLO
- VLO = 8MHz/counts


 **Library coming soon!**

Demo: LPM3 Using VLO

```
void main(void)
{
    BCSTL3 |= LFXT1S_2;           // LFXT1 = VLO
    WDTCTL = WDT_ADLY_1000;
    IE1 |= WDTIE;
    // Configure P1/P2
    for (;;) {
        _BIS_SR(LPM3_bits + GIE); // Enter LPM3
        P1OUT ^= 0x01;
    }
}
#pragma vector=WDT_VECTOR
__interrupt void watchdog_timer(void) {
    _BIC_SR_IRQ(LPM3_bits);       // Clear LPM3 bits 0(SR)
}
```

- What is the measured current consumption?

F2xx Expanded Operating Range



© 2006 Texas Instruments Inc, Slide 15


F2xx: More Robust

WDT+:

- Watchdog or interval timer
- Selectable intervals
- Password protected
- **Failsafe/protected clock**


System Enhancements:

- **Blank device > LPM4**
- **Invalid address reset**
- **BOR on every 2xx**



© 2006 Texas Instruments Inc, Slide 16

All F2xx Have Zero Power BOR




- MSP430 BOR is always-on and zero-power

Agenda

- Enhancements
- Application Examples
- Devices & Summary


F20x1 Tiny Power Saver




- **<1uA RTC Function**
- **DSP Power Sequencing**
- **Vcc Monitoring**
- **User Interface**
- **Tiny 4x4mm Footprint**

F2xx Comparator A+

- Slope ADC
- Battery detect
- Reference generator
- Interrupt source
- Timer_A capture
- **Expanded input multiplexer**
- **Multiplexer short for sample-and-hold**




F20x1 Residential Thermostat



- **<1uA total system power**
- **10-bit slope ADC**
- **$\pm 1\text{C/F}$**
- **No XTAL needed**
- **Very low cost**

F2xx OA

- Single-supply
- Low-current
- Rail-Rail output
- Selectable settling time vs. current consumption
- Integrated R-ladder for PGA function
- 5 modes
 - GP
 - Unity buffer
 - Comparator
 - NI PGA
 - Inverting PGA




© 2006 Texas Instruments Inc, Slide 22

 **MSP430F22x4**

F22x4 Glass Break Detector


- Integrated Solution
- 2ms sample interval
- VLO – no crystal required
- 50uA average current
- Real-time signal analysis




ADC10

- 10-bit ADC
- 200ksps+
- Autoscan
- Single Sequence Repeat-single Repeat-sequence
- Int/ext ref
- TA SOC triggers
- Data transfer controller

➔ 14-pin MSP430F2012



F20x2 Low-Cost Smoke Detector




- 8s sample interval
- 2uA average system power
- VLO – no crystal required


SD16 A

- 16-bit $\Sigma\Delta$ ADC
- 4.096 ksps
- Differential inputs
- 85db SINAD
- 32x PGA
- 18ppm 1.2V ref
- Temp sensor

 **14-pin MSP430F2013**



F20x3 PIR Motion Detector



< 7uA total system power

- ~5uA PIR
- ~1uA Measurement
- ~0.5uA MSP430 LPM3

• Fully programmable


- Single-chip solution
- Direct interface to SD16
- VLO – no XTAL required

• Lower cost

© 2006 Texas Instruments Inc, Slide 27


F20x2/3 Universal Serial Interface

- Reduces CPU load
- SPI Mode
 - 8/16-bit Shift Register
 - MSB/LSB first
- I²C Mode Support
 - START/STOP detection
 - SCL held after START
 - SCL held after counter overflow
 - Arbitration lost detection
- Fully Static Design
- Interrupt Driven




Data I/O

- Data shift register: up to 16 bits supported
- Number of bits TX'd & RX'd controlled by bit counter
- TX & RX is simultaneous
- Data I/O is user-defined: MSB or LSB first
- Bit counter automatically stops clocking after last bit & sets flag
- No data buffering!



USI Reduces CPU Load for SPI




```
//Shift16_inout_Software
SR = DATA;
for (CNT=0x10;CNT>0;CNT--)
{
    P2OUT &= ~SDO;
    if (SR & 0x8000)
        P2OUT |= SDO;
    SR = SR << 1;
    if (P2IN & SDIN)
        SR |= 0x01;
    P2OUT |= SCLK;
    P2OUT &= ~SCLK;
}
```

425 Cycles

```
// Shift16_inout_USI
USISR |= DATA;
USICNT |= 0x10;
```


10 Cycles

F20x2/3 USI Enables Practical I2C



- I2C Slave has as little as **4us** from clock edge to data
- **Traditional software**-only solution allows for little else
- USI **hardware** enables practical and compliant I2C
- Code examples on the web


USI Clock Control



- **Multiplexed input from up to 8 int/ext sources**
- **Configurable divider**
- **Auto-stop on interrupt: USIIFG**
- **Selectable phase and polarity**
- **Software clock: USISWCLK clock input bit**

Universal Serial Communication I/F

- **Ultra-low power**
 - LPMx operation
- **2 individual blocks**
- **Double buffered TX/RX**
- **RX glitch suppression**
- **Baud rate generator**
 - Flexible clock source
 - Automatic detection
 - Generation
- **DMA enabled**
- **Interrupt driven**




© 2006 Texas Instruments Inc, Slide 33

USCI Enhanced Features


- **New standard MSP430 serial interface**
- **Auto clock start from any LPMx**
- **Two independent communication blocks**
- **Asynchronous communication modes**
 - UART standard and multiprocessor protocols
 - UART with automatic Baud rate detection (LIN support)
 - Two modulators support n/16 bit timing
 - IrDA bit shaping encoder and decoder
- **Synchronous communication modes**
 - SPI (Master & Slave modes, 3 & 4 wire)
 - I2C (Master & Slave modes)

USCI_A



- **UART with IrDA/LIN support or SPI**
- **Double buffered TX/RX**
- **Baud-rate generator with auto-baud rate detect**

USCI_B




- I2C master/slave up to 400kHz or SPI
- Bit clock generator
- Double buffered TX/RX

New MSP430X CPU

- Architecture upgrade
- 100% code compatible
- 1MB unified memory map
- **Extended addressing modes**
 - Page-free 20-bit reach
 - Improved code density
 - Faster execution

 **MSP430F241x/261x**



© 2006 Texas Instruments Inc, Slide 37



F2xx: Every Little Bit Counts

- Pull-up/down pin resistors

MIN	TYP	MAX	
20	35	50	K Ω

- XTAL capacitors

- DCO and VLO oscillators



Agenda

- Enhancements
- Application Examples
- Devices & Summary

New F2xx Multi-Purpose Devices

Device	Pins	Flash/RAM	Features	Samples
F20x1	14	2KB / 128B	TA2, Comp_A	Now
F20x2	14	2KB / 128B	TA2, USI, AC10	Now
F20x3	14	2KB / 128B	TA2, USI, SD16	Now
F21x1	20	8KB / 256B	TA3, Comp_A	Now
F22x2*	38/40	32KB / 1KB	TA3, TB3, USCI, ADC10	Now
F22x4*	38/40	32KB / 1KB	TA3, TB3, USCI, ADC10, (2)OPA	Now
F23x0*	40	32KB / 2KB	TA3, TB3, USCI, Comp_A, MPY	1Q07
F23x*	64	16KB/512B	TA3, TB3, USCI, ADC12	2Q07
F24x*	64	60KB/2KB	TA3, TB7, (2)USCI, ADC12	2Q07
F241x*	64/80	120KB / 8KB	TA3, TB7, (2)USCI, ADC12,MPY	1Q07
F261x*	64/80	120KB / 8KB	TA3, TB7, (2)USCI,ADC12, MPY, (2)DAC12, (3)DMA	1Q07
All devices include enhanced watchdog timer (WDT+) and enhanced basic clock system (BCS+)				
* Planned Future device, in development				

Summary

- **Pin-compatible drop-ins**
- **Lower Power**
- **Faster**
- **Many upgraded peripherals**
- **Many new devices**

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
Low Power Wireless	www.ti.com/lpw

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2007, Texas Instruments Incorporated